


CLASSTIG 180E



- ☐ HF Mode-High Frequency TIG Mode
- ☐ Selectable Post Flow time
- ☐ High duty cycle for industrial applications
- ☐ Compact and portable with light weight
- ☐ 2T/4T mode for earlier working Except TIG180E
- ☐ Selectable down slope time (Except TIG 180E)
- ☐ Generator friendly allows to work with diesel generators and to avoid failures due to its voltage spikes
- ☐ Protections including over-heat ,over-voltage,low-voltage and over-current

Decoration Industrial **DC 1** Phase

Processes

- TIG(GTAW)
- STICK(SMAW)

Optional Accessories

- Earth cable and clamp
- Welding cable and holder
- Suitcase
- Lift TIG Torch
- Regulator

MODEL	CLASSTIG 180 E
Power Supply Voltage (V)	160-275
Fre.(HZ)	50/60
Function	TIG
Rated Input Power (KW)	3.9
Rated Input Current (A)	25
Duty Cycle (40°C 10min)	40% 180A 100% 115A
No Load Voltage (V)	60
Welding Current Range (A)	10-180
Net Weight (KG)/(LB)	4.5 KG/9.9 LB
Dimensions (MM)/(Inch)	280*127*210/11*5*8.3
Welding Voltage Range (V)	0-5
Power Factor	0.75

www.crepow.com
Choice Prove Tig Series

CE RoHS

CREPOW®
Welding & Cutting Technology